

## 250ME Electrically Operated Stat-X Aerosol Generator

Part No. 15530



**Aerosol nominal mass:** 250 grams

**Weight:** 1.36 kg / 2.99 lbs.

**Length:** 205 mm / 8.063 inches

**Diameter:** 76 mm/ 3 inches

**Discharge time:** 18 seconds

**Initiation current:** .5 AMP parallel and 1 AMP in series

**Maximum allowable supervisory current on a release circuit:** .005 AMP

### Operation/Storage Parameters:

Temperature	-40 <sup>0</sup> C to +54 <sup>0</sup> C (-40 <sup>0</sup> F to +130 <sup>0</sup> F)
Relative Humidity	up to 98% at +35 <sup>0</sup> C (+95 <sup>0</sup> F)

### Dangerous Goods Transportation Classification:

For transporting by public highway, rail, marine vessel or cargo aircraft only: Special Permit DOT-SP 20600 authorizes transport as Proper Shipping Name: UN3268 Safety Devices 9.

For shipment by air (cargo or passenger): International Air Transport Association (IATA) regulations authorize the Proper Shipping Name: UN0432 Articles pyrotechnic 1.4S

### Shipping Limitations:

Ground: Placards required for any shipment of > 1001 lbs. as UN0432 1.4S

Max. Net Qty/Pkg- Cargo Air 100 kgs (220 lbs)

Max. Net Qty/Pkg- Passenger Air 25 kgs (55 lbs)

