

# Digital Linear Heat Detection Cable 88° with Nylon Alarmline II Series



## Overview

The Digital Linear Heat Detection (LHD) cable with a 88°C fixed temperature activation rating has a nylon outer sheath for UV protection and increased durability for external applications. It is supplied in 100m, 500m and 1,000m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

## Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input, ie. conventional detection zone or addressable interface unit.

## Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

## Cable fixings for all applications

A range of 'edge', 'A', 'P' and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.

## Standard Features

- cUL/UL 521 approved
- FM approved (Class 3210)
- Up to 3,000m per zone
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas



**Australia & New Zealand**

Phone: 1800 672 171  
Outside Australia: +61 3 9518 5588  
Email: firesecuritycs@carrier.com  
Web: www.kidde.com.au

**Head Office**

10 Ferntree Place  
Notting Hill, Victoria 3168  
Australia

© 2020 Carrier. All rights reserved.  
Kidde Australia is a Carrier company.

Specifications

	100m	500m	1,000m
<b>Mechanical</b>			
Outside diameter (Nominal)		4.44mm ± 0.12mm	
No of cores		2	
Colour		Black	
Weight	2.52kg	12.6kg	25.2kg
<b>Electrical</b>			
Operating voltage		0 to 30VAC, 0 to 42 VDC	
Conductor resistance		~ 100 ohms/km per leg (30.4 ohms/kft)	
Capacitance		88 to 150pF/m	
Inductance		540 to 1050nH/m	
<b>Environmental</b>			
Ambient temperature (max)		45°C	
Relative humidity		0% to 100%	

Ordering information

Part number	Description
AD88N-0100	Alarmline II Digital LHD Cable 88°C with Nylon Sheath - 100m
AD88N-0500	Alarmline II Digital LHD Cable 88°C with Nylon Sheath - 500m
AD88N-1000	Alarmline II Digital LHD Cable 88°C with Nylon Sheath - 1000m
ADLCU	Linear Heat Detection, Digital LHD Control Unit