

## ADELUCU-EOL

### Alarmline II Digital EN - Spare end-of-line unit



### General

Replacement end-of-line unit for use with the AlarmLine II Digital EN Linear Heat Detection Controller and AlarmLine II Digital EN Linear Heat Detection Cable.

### Functional testing

Internally the unit features 4 switches, which can be used to simulate a fire or fault on each of the zones. There are two push-buttons, one for each zone, which simulate a fire by connecting the two cable cores when the button is pressed. Similarly there are two switches, which under normal conditions connect the end-of-line resistor across the cable, for each zone. However when the switch is changed, this create an open circuit which in turn raises a fault on the controller. Via these switches it is easy to functionally test the system.

### Details

- Quickly simulate a fault condition
- Quickly simulate an alarm condition
- Supplied with 2 IP67 rated cable glands
- Secure, weatherproof enclosure
- RoHS Compliant, CE & EN54-28:2016 Certified



### Australia & New Zealand

Phone: 1800 672 171

Outside Australia: +61 3 9518 5588

Email: firesecuritycs@carrier.com

Web: www.kidde.com.au

### Head Office

10 Ferntree Place

Notting Hill, Victoria 3168

Australia

© 2021 Carrier. All rights reserved.  
Kidde Australia is a Carrier company.

---

## Technical specifications

---

### Physical

Physical dimensions	94 x 94 x 57 mm (W x H x D)
---------------------	-----------------------------

Terminals	5 mm rising clamp
-----------	-------------------

### Environmental

Operating temperature	-35 to +55°C
-----------------------	--------------

IP rating	IP66
-----------	------

### Standards & regulation

Certification	CE, EN54-28
---------------	-------------

---