







## KIT OVERVIEW CATALOGUE

## **ELECTRIC PANEL PROTECTION KITS**

DOC - CTG0018 01 SEPTEMBER 2020 - REV B













# **RE2001**



#### 1 x 1.0KG DIRECT 3M™ NOVEC™ 1230 COMPLETE KIT

#### **DESCRIPTION**

#### **BASIC SYSTEM CONFIGURATION**

The 1.0kg Direct 3M<sup>™</sup> Novec<sup>™</sup> 1230 kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 1.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-014-010-FK5 | 15 bar CE - 1.0kg CT Direct 3M™ Novec™ 1230 System |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 7   | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 1   | RE7041            | QR Twinseal Stud: 1/8" Threaded - 4/6mm Tube       |
| 36  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7205            | 1.4Lt (1kg) Wire Bracket                           |
| 10  | RE7211            | R80 4/6 RED Detection Tube                         |
| 34  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |

# **RE2002**



#### 1 x 2.0KG DIRECT 3M™ NOVEC™ 1230 COMPLETE KIT

#### **DESCRIPTION**

#### **BASIC SYSTEM CONFIGURATION**

The 2.0kg Direct  $3M^{\text{\tiny IM}}$  Novec  $^{\text{\tiny IM}}$  1230 kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 2.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-026-020-FK5 | 15 bar CE - 2.0kg CT Direct 3M™ Novec™ 1230 System |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 7   | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 1   | RE7041            | QR Twinseal Stud: 1/8" Threaded - 4/6mm Tube       |
| 36  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7207            | 2.6Lt (2kg) Wire Bracket                           |
| 10  | RE7211            | R80 4/6 RED Detection Tube                         |
| 34  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



#### 1 x 3.0KG DIRECT 3M™ NOVEC™ 1230 COMPLETE KIT

#### **DESCRIPTION**

#### **BASIC SYSTEM CONFIGURATION**

The 3.0kg Direct  $3M^{"}$  Novec" 1230 kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 3.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-048-030-FK5 | 15 bar CE - 3.0kg CT Direct 3M™ Novec™ 1230 System |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 14  | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 2   | RE7008            | QR Twinseal Tee: - 4/6mm Tube Only                 |
| 1   | RE7013            | QR Twinseal Tee: 1/8" Threaded - 4/6mm Tube        |
| 69  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7223            | Standard Bracket                                   |
| 20  | RE7211            | R80 4/6 RED Detection Tube                         |
| 67  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



#### 1 x 4.0KG DIRECT 3M™ NOVEC™ 1230 COMPLETE KIT

#### **DESCRIPTION**

### **BASIC SYSTEM CONFIGURATION**

The 4.0kg Direct  $3M^{\infty}$  Novec<sup> $\infty$ </sup> 1230 kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 4.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-048-040-FK5 | 15 bar CE - 4.0kg CT Direct 3M™ Novec™ 1230 System |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 14  | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 2   | RE7008            | QR Twinseal Tee: - 4/6mm Tube Only                 |
| 1   | RE7013            | QR Twinseal Tee: 1/8" Threaded - 4/6mm Tube        |
| 69  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7223            | Standard Bracket                                   |
| 20  | RE7211            | R80 4/6 RED Detection Tube                         |
| 67  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



## 1 x 6.0KG DIRECT 3M™ NOVEC™ 1230 COMPLETE KIT

#### **DESCRIPTION**

#### **BASIC SYSTEM CONFIGURATION**

The 6.0kg Direct  $3M^{"}$  Novec" 1230 kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 6.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-075-060-FK5 | 15 bar CE - 6.0kg CT Direct 3M™ Novec™ 1230 System |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 20  | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 2   | RE7008            | QR Twinseal Tee: - 4/6mm Tube Only                 |
| 1   | RE7013            | QR Twinseal Tee: 1/8" Threaded - 4/6mm Tube        |
| 102 | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7224            | Standard Bracket                                   |
| 30  | RE7211            | R80 4/6 RED Detection Tube                         |
| 100 | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |

# **RE2011**



#### 1 x 1.0KG DIRECT FM-200™ COMPLETE KIT

#### **DESCRIPTION**

#### **BASIC SYSTEM CONFIGURATION**

The 1.0kg Direct FM-200" kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 1.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-014-010-HFC | 15 bar CE - 1.0kg CT Direct FM-200™ System         |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 7   | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 1   | RE7041            | QR Twinseal Stud: 1/8" Threaded - 4/6mm Tube       |
| 36  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7205            | 1.4Lt (1kg) Wire Bracket                           |
| 10  | RE7211            | R80 4/6 RED Detection Tube                         |
| 34  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



#### 1 x 2.0KG DIRECT FM-200™ COMPLETE KIT

#### **DESCRIPTION**

#### **BASIC SYSTEM CONFIGURATION**

The 2.0kg Direct FM-200™kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 2.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-026-020-HFC | 15 bar CE - 2.0kg CT Direct FM-200™ System         |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 7   | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 1   | RE7041            | QR Twinseal Stud: 1/8" Threaded - 4/6mm Tube       |
| 36  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7207            | 2.6Lt (2kg) Wire Bracket                           |
| 10  | RE7211            | R80 4/6 RED Detection Tube                         |
| 34  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



#### 1 x 3.0KG DIRECT FM-200™ COMPLETE KIT

#### **DESCRIPTION**

The 3.0kg Direct FM-200™ kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 3.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .

#### **BASIC SYSTEM CONFIGURATION**



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-048-030-HFC | 15 bar CE - 3.0kg CT Direct FM-200™ System         |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 14  | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 2   | RE7008            | QR Twinseal Tee: - 4/6mm Tube Only                 |
| 1   | RE7013            | QR Twinseal Tee: 1/8" Threaded - 4/6mm Tube        |
| 69  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7223            | Standard Bracket                                   |
| 20  | RE7211            | R80 4/6 RED Detection Tube                         |
| 67  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



#### 1 x 4.0KG DIRECT FM-200™ COMPLETE KIT

#### **DESCRIPTION**

### **BASIC SYSTEM CONFIGURATION**

The 4.0kg Direct FM-200™ kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 4.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-048-040-HFC | 15 bar CE - 4.0kg CT Direct FM-200™ System         |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 14  | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 2   | RE7008            | QR Twinseal Tee: - 4/6mm Tube Only                 |
| 1   | RE7013            | QR Twinseal Tee: 1/8" Threaded - 4/6mm Tube        |
| 69  | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7223            | Standard Bracket                                   |
| 20  | RE7211            | R80 4/6 RED Detection Tube                         |
| 67  | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |



#### 1 x 6.0KG DIRECT FM-200™ COMPLETE KIT

#### **DESCRIPTION**

The 6.0kg Direct FM-200™ kit has been configured for your Electrical Control Panel applications.

The kit is for volumes up to 6.0m3

All kits come complete with a factory filled and pressurised cylinder, Pressure Switch, cylinder bracket and all fittings, fixings & labels for a successful installation.

Items such as Sounders & Beacons will need to be added separately.

If the system is to comply with LPCB (LPS 1666) please consult Reacton Fire Suppression Ltd .

#### **BASIC SYSTEM CONFIGURATION**



| QTY | PART NUMBER       | DESCRIPTION  |
|-----|-------------------|--|
| 1   | RE-CT-075-060-HFC | 15 bar CE - 6.0kg CT Direct FM-200™ System         |
| 1   | RE5002            | Pressure Switch - N/O&N/C 9Bar F, 1/8", 20cm Cable |
| 1   | RE6110            | Reacton Branded Adhesive Caution Label A5          |
| 20  | RE6111            | Reacton Branded Adhesive Do not Kink Label 58 x 72 |
| 1   | RE6113            | Reacton Adhesive Cylinder Maintenance Label A5     |
| 1   | RE6420            | Anti Tamper Lock for Mini Ball Valve               |
| 2   | RE7008            | QR Twinseal Tee: - 4/6mm Tube Only                 |
| 1   | RE7013            | QR Twinseal Tee: 1/8" Threaded - 4/6mm Tube        |
| 102 | RE7079            | Self Drilling Screw, Hex 8mm x 25mm                |
| 1   | RE7086            | Double Ended Cable Ties - BLACK 300x4.8mm          |
| 1   | RE7126            | Tamper Seal  |
| 1   | RE7224            | Standard Bracket                                   |
| 30  | RE7211            | R80 4/6 RED Detection Tube                         |
| 100 | RE7232            | P-Clips: Steel Rubber Lined 6mm                    |
| 1   | RE7234            | Component Bracket 58mmx58mmx3mm                    |
| 1   | RE7243            | End of the Line (EOL): 4/6mm Tube                  |

# REACTON FIRE SUPPRESSION

Protecting your future, today



#### **REACTON EUROPE**

Address: 14 Baynes Place, Waterhouse Business Park, Chelmsford,

Essex, CM1 2QX, United Kingdom

Phone: +44 (0) 1245 930 296 email: info@reactonfire.com www.reactonfire.com web:

#### **REACTON NORTH AMERICA**

AZ 85027, USA

Address: 23335 N 18th Dr #140, Phoenix,

Phone: +1 844 732 2866

info@reactonfire.com email: web: www.reactonfire.com

#### **REACTON UNITED ARAB EMIRATES**

Address: Business Center, Building A3, Dubai World Central,

Dubai, United Arab Emirates

+971 50 236 2357 Phone: email: info@reactonfire.ge web: www.reactonfire.ae



#### **REACTON SYSTEMS PROTECT**

- On-Road and Off-Road Vehicles
- Residential Kitchens
- Manufacturing and Machining Equipment
- Industrial Equipment
- Heavy Equipment
- Power Generation
- Data Centres
- **Electrical Control Cabinets**



















